



INSTALLATION INSTRUCTIONS FOR DISPOSAL INSTALLATION TOOL

Visit
DANCO.COM
for Easy D.I.Y. Solutions

To Install Flange

Tools Required: Plumber's Putty, Screwdriver

1. Apply plumber's putty around the disposal flange and press it into place.
2. Set new garbage disposal unit directly below the flange opening.
3. Set the Under-Sink Flange assembly on top of the new garbage disposal in this order: Snap Ring on bottom, Mounting Flange next, then Backup Flange last (on top of the other 2 pieces).
4. From above the sink opening drop the Hook through the new flange and down into the garbage disposal chamber until the hook is completely inside and hanging freely.
5. Then slowly but firmly lift on chain until Hook is centered inside disposal, then lift disposal unit by pulling chain up through the opening from above the sink. Slide one of the links of the chain into the flat Lock Bar to lock the disposal in place 2-3 inches below the flange to give your hands a place to rest as you install the under-sink assembly of the flange.
6. Ensuring that **no part of your body is below the disposal** rest your hands on the top of the disposal and use one hand to lift the Backup Flange and the Mounting Flange into place around the Sink Flange. While holding the Backup Flange and Sink Flange in place with one hand use the other hand to lift the Snap Ring into place, then while holding the Backup Flange and Sink Flange in place with the back of your hands slide the Snap Ring onto the bottom of the Sink Flange...this will take some effort to open the split ring, but the weight of the disposal should hold down the Sink Flange while you press upward on the Snap Ring.
7. Once you hear the Snap Ring snap into place, align the mounting flange so that the 3 screws are lined up to screw onto the Backup Flange, then hand tighten.
8. After making sure the Sink Flange is aligned, tighten the 3 screws on the Mounting Flange with a screwdriver.

To Install Disposal

1. Lower Hook into top of garbage disposal by turning sideways and dropping Hook all the way down from the drain opening above into the grinding chamber, making sure Hook swings loosely on chain.
2. Gently at first, then firmly, pull up on chain, making sure Hook is centered in disposal opening. Lift through sink drain and center disposal on flange, applying upward tension on spring.
3. Slide flat lock across drain opening, inserting chain into notch on the Lock Bar, maintaining tension on the spring.
4. Engage locking ring on underside of sink to secure disposal (by lifting it and turning it counter-clockwise so that the 3 locking tabs catch the flange above and tighten it counter clockwise. (most models)).
5. Holding firmly on chain, slide chain out of the notch in the locking bar, remove tool, placing Hook/Chain assembly and lock safely away from sink area before connecting electrical power to disposal.

*To remove an existing disposal **MAKE SURE** disposal power switch is taped in **OFF** position and power is **DISCONNECTED**. Then perform steps of installation (listed above) in reverse order.

